

DALLAS
SEMICONDUCTOR

DS1287
Real Time Clock

FEATURES

- Drop-in replacement for IBM AT computer clock/calendar
- Pin compatible with the MC146818A
- Totally nonvolatile with over 10 years of operation in the absence of power
- Self-contained subsystem includes lithium, quartz, and support circuitry
- Counts seconds, minutes, hours, day of the week, date, month, and year with leap year compensation
- Binary or BCD representation of time, calendar, and alarm
- 12- or 24-hour clock with AM and PM in 12-hour mode
- Daylight Savings Time option
- Selectable between Motorola and Intel bus timing
- Multiplex bus for pin efficiency
- Interfaced with software as 64 RAM locations
 - 14 bytes of clock and control registers
 - 50 bytes of general purpose RAM
- Programmable square wave output signal
- Bus-compatible interrupt signals ($\overline{\text{IRQ}}$)
- Three interrupts are separately software-maskable and testable
 - Time-of-day alarm once/second to once/day
 - Periodic rates from 122 μs to 500 ms
 - End of clock update cycle

DESCRIPTION

The DS1287 Real Time Clock is designed to be a direct replacement for the MC146818A. For a complete description of operating conditions, electrical and

PIN ASSIGNMENT

MOT	1	24	V _{CC}
NC	2	23	SQW
NC	3	22	NC
AD0	4	21	NC
AD1	5	20	NC
AD2	6	19	$\overline{\text{IRQ}}$
AD3	7	18	$\overline{\text{RESET}}$
AD4	8	17	DS
AD5	9	16	NC
AD6	10	15	R/ $\overline{\text{W}}$
AD7	11	14	AS
GND	12	13	$\overline{\text{CS}}$

24 PIN ENCAPSULATED PACKAGE

PIN DESCRIPTION

AD0–AD7	- Multiplexed address/data bus
NC	- No connection
MOT	- Bus type selection
$\overline{\text{CS}}$	- Chip select
AS	- Address strobe
R/ $\overline{\text{W}}$	- Read/write input
DS	- Data strobe
$\overline{\text{RESET}}$	- Reset input
$\overline{\text{IRQ}}$ drain)	- Interrupt request output (open drain)
SQW	- Square wave output
V _{CC}	- +5 volt supply
GND	- Ground

mechanical characteristics, bus timing, and pin descriptions see the DS12887 data sheet.