
Q3/94

PCWARE INTERNATIONAL, INC. VL IDE & I/O CONTROLLER

Data bus: Size: Hard drive supported: Floppy drives supported:

32-bit VESA Full-length, Full-height card 2 IDE(AT) interface drives 360KB, 720KB, 1.2MB, 1.44MB



Function	Location	Setting
í Factory configured - do not alter	J3	N/A
í Factory configured - do not alter	J4	N/A
í IDE(AT) interface enabled	J7	pins 1 & 2 closed
IDE(AT) interface disabled	J7	pins 2 & 3 closed
í Parallel port enabled	J11	pins 1 & 2 closed
Parallel port disabled	J11	pins 2 &3 closed
í Factory configured - do not alter	J12	pins 2 & 3 closed

Continued on next page. . .

Copyright © 1991, 1992, 1993 by Micro House Int'I (800) 926-8299. Research Dept. (303) 443-3389

PCWARE INTERNATIONAL, INC. VL IDE & I/O CONTROLLER

... continued from previous page

USER CONFIGURABLE SETTINGS(CONTINUED)						
Function	Location	Setting				
í Serial port 1 enabled	J13	pins 1 & 2 closed				
Serial port 1 disabled	J13	pins 2 & 3 closed				
í Serial port 1 COM1 select	J14	pins 1 & 2 closed				
Serial port 1 COM3 select	J14	pins 2 & 3 closed				
í Serial port 2 enabled	J15	pins 1 & 2 closed				
Serial port 2 disabled	J15	pins 2 & 3 closed				
í Floppy drive interface enabled	J16	pins 1 & 2 closed				
Floppy drive interface disabled	J16	pins 2 & 3 closed				
í Parallel port address LPT2 select	J17	pins 1 & 2 closed				
Parallel port address LPT3 select	J17	pins 2 & 3 closed				
í Serial port 2 COM2 select	J18	pins 1 & 2 closed				
Serial port 2 COM4 select	J18	pins 2 & 3 closed				
í Game port enabled	J19	pins 1 & 2 closed				
Game port disabled	J19	pins 2 & 3 closed				

33MHZ ACTIVE/RECOVERY TIME					
Active	Recovery	J5	J8	J 9	J10
5T	5T	open	open	open	open
5T	7T	open	closed	open	open
5T	9T	open	open	closed	open

50MHZ ACTIVE/RECOVERY TIME					
Active	Recovery	J5	J8	J9	J10
9T	9T	closed	open	closed	open
9T	11T	closed	closed	closed	open
9T	13T	closed	open	open	closed

Copyright \circledcirc 1991, 1992, 1993 by Micro House Int'l (800) 926-8299. BBS (303) 443-9957