


SCI SYSTEMS, INC.

TC316SX/TC320SX/TC325SX

| | |
|--------------------------|--|
| Processor | 80386SX |
| Processor Speed | 16/20/25MHz |
| Chip Set | VLSI Topcat |
| Max. Onboard DRAM | 16MB |
| Cache | None |
| BIOS | AMI |
| Dimensions | 330mm x 218mm |
| I/O Options | Bus mouse port, floppy drive interface, IDE interface, parallel port, serial ports (2), VGA port |
| NPU Options | 80387SX |



CONNECTIONS

| Purpose | Location | Purpose | Location |
|------------------------|----------|---------------------|----------|
| Serial port (COM1) | P3 | VGA port | P10 |
| Parallel port | P4 | Reset switch | P11 |
| Floppy drive interface | P5 | Speaker | P12 |
| IDE interface | P6 | Power LED & keylock | P13 |
| Serial port (COM2) | P7 | Turbo LED | P14 |
| PS/2 bus mouse | P9 | IDE interface LED | P15 |

Continued on next page . . .

SCI SYSTEMS, INC.

TC316SX/TC320SX/TC325SX

... continued from previous page

| USER CONFIGURABLE SETTINGS | | |
|--|---------------|-------------------|
| Function | Jumper/Switch | Position |
| í VGA interrupt request generation disabled | JP1 | pins 1 & 2 closed |
| VGA interrupt request generation enabled | JP1 | pins 2 & 3 closed |
| í VGA port enabled | JP2 | pins 2 & 3 closed |
| VGA port disabled | JP2 | pins 1 & 2 closed |
| í IDE drive installed select 1 | JP3 | pins 1 & 2 closed |
| IDE drives installed select 2 | JP3 | pins 2 & 3 closed |
| í Pipeline mode enabled | JP4 | pins 2 & 3 closed |
| Pipeline mode disabled | JP4 | pins 1 & 2 closed |
| í Floppy drive generation of disk change signal disabled | JP5 | pins 1 & 2 closed |
| Floppy drive generation of disk change signal enabled | JP5 | pins 2 & 3 closed |
| í Monitor type select color | JP6 | pins 1 & 2 closed |
| Monitor type select monochrome | JP6 | pins 2 & 3 closed |
| í CMOS memory normal operation | JP7 | pins 2 & 3 closed |
| CMOS memory clear | JP7 | pins 1 & 2 closed |
| í Factory configured - do not alter | SW1/switch 1 | open |
| í Factory configured - do not alter | SW1/switch 2 | closed |
| í Video mode select 1024x768 pixel resolution interlaced | SW1/switch 5 | closed |
| Video mode select 1024x768 pixel resolution non-interlaced | SW1/switch 5 | open |

| DRAM CONFIGURATION | | |
|--------------------|--------------|--------------|
| Size | Bank 0 | Bank 1 |
| 512KB | (2) 256K x 9 | NONE |
| 1MB | (2) 256K x 9 | (2) 256K x 9 |
| 2MB | (2) 1MBx 9 | NONE |
| 2.5MB | (2) 1MBx 9 | (2) 256K x 9 |
| 4MB | (2) 1MBx 9 | (2) 1MBx 9 |
| 8MB | (2) 4MB x 9 | NONE |
| 8.5MB | (2) 4MB x 9 | (2) 256K x 9 |
| 10MB | (2) 4MB x 9 | (2) 1MBx 9 |
| 16MB | (2) 4MB x 9 | (2) 4MB x 9 |

| VIDEO CONFIGURATION | | |
|--|-------|-------|
| Setting | SW1/3 | SW1/4 |
| 800x600 with 16 colors at 60Hz/800x600 with 256 colors at 56Hz | On | On |
| 800x600 with 16 colors at 72Hz/800x600 with 256 colors at 56Hz | Off | On |

| VIDEO CONFIGURATION | | |
|---------------------|-------|-------|
| Setting | SW1/3 | SW1/4 |
| 800x600 at 60Hz | On | Off |
| 800x600 at 56Hz | Off | Off |