


ZEOS INTERNATIONAL, LTD.

UPGRADABLE SYSTEMS MAINBOARD

Processor	80386/80486SX/80487SX/80486DX (On proprietary CPU cards)
Processor Speed	20/25/33MHz
Chip Set	Unidentified
Max. Onboard DRAM	32MB
Cache	128KB
BIOS	Award
Dimensions	330mm x 218mm
I/O Options	floppy drive interface, game port, IDE interface, parallel port, serial ports (2), proprietary CPU card slot
NPU Options	80387



CONNECTIONS			
Purpose	Location	Purpose	Location
External battery	J1	Turbo switch	J10
Game port	J3	Reset switch	J11
Parallel port	J5	Turbo LED	J12
Serial port 2	J6	Power LED & keylock	J13
Serial port 1	J7	Speaker	J14
Floppy drive interface	J8	IDE interface LED	J15
IDE interface	J9	Proprietary CPU card slot	CPU1 & CPU2

Continued on next page. . .

ZEOS INTERNATIONAL, LTD.

UPGRADABLE SYSTEMS MAINBOARD

... continued from previous page

USER CONFIGURABLE SETTINGS		
Function	Jumper	Position
í Monitor type select CGA	J4	Closed
Monitor type select Mono/EGA/VGA	J4	Open
í Game port enabled	P1	Closed
Game port disabled	P1	Open
í Parallel port interrupt select IRQ7	PIRQ	pins 1 & 2 closed
Parallel port interrupt select IRQ5	PIRQ	pins 2 & 3 closed
Parallel port interrupt disabled	PIRQ	all open
í Serial port 1 (COM1) interrupt select IRQ4	SIRQ1	pins 2 & 3 closed
Serial port 1 (COM1) interrupt select IRQ3	SIRQ1	pins 1 & 2 closed
Serial port 1 (COM1) interrupt disabled	SIRQ1	all open
í Serial port 2 (COM2) interrupt select IRQ3	SIRQ2	pins 1 & 2 closed
Serial port 2 (COM2) interrupt select IRQ4	SIRQ2	pins 2 & 3 closed
Serial port 2 (COM2) interrupt disabled	SIRQ2	all open

DRAM CONFIGURATION		
Size	Bank 0	Bank 1
1MB	(4) 256K x 9	NONE
2MB	(4) 256K x 9	(4) 256K x 9
4MB	(4) 1M x 9	NONE
5MB	(4) 1M x 9	(4) 256K x 9
8MB	(4) 1M x 9	(4) 1M x 9
16MB	(4) 4M x 9	NONE
20MB	(4) 4M x 9	(4) 1M x 9
32MB	(4) 4M x 9	(4) 4M x 9