



***Model: AM-571***

## **TX Pro II Pentium Motherboard**



### *Technical Specifications*

#### **CPU**

Pentium™ Processor at 75-233MHz.  
Intel® Pentium™ P54C and P55C (MMX),  
Cyrix™/IBM™ 6x86/6x86L, MX, MXII  
IDT C6,  
AMD™ K5/K6.

#### **Cache Memory**

Onboard 512KB Pipelined Burst Synchronous L2 Cache

#### **Chipset**

TX PRO II

#### **BIOS**

1MB Flash EPROM  
IDE AUTO LBA Mode Supports HDDs over 8.4GB  
Anti-Virus Protection

#### **System Memory**

2x168-pin DIMMs  
4x72-pin SIMMs  
Supports SDRAM & 3.3V EDO  
Up to 384MB

#### **Expansion Slots**

3xISA Bus Slots (1 ISA Slot Shared With 1 PCI Slot)  
4xPCI Bus Slots (1 PCI Slot Shared With 1 ISA Slot)

#### **Onboard I/O**

Support Two PCI EIDE PIO Mode3, Mode4 and Ultra DMA 33 HDDs  
Twin Headers for Four IDE Device  
Supports Two FDDs  
One ECP/EPP Parallel Port, Two 16550 UART Serial Ports, Two USB Ports  
(Optional ATX Form Factor Card)  
PS/2 Mouse Port (Optional Adapter Cable), Keyboard Port, IrDA Port (Optional  
TX/RX Module)

### **Onboard VGA**

Built-in high performance 64-bit Graphics Accelerator with 4MB Shared Memory  
Fram Buffer

### **Onboard Sound**

3D Sound Pro Chipset Supports HRTF Positional Audio  
Direct Sound & Software Wavetable Synthesizer, Digital Audio Interface (SPDIF  
IN/OUT)  
Supports SB16, WSS & Game

### **Plug and Play**

Plug and Play Specification 1.1  
Plug and Play for DOS®, Windows® 3.x and Windows® 95

### **Other Features**

Supports ACPI and Legacy PMU  
Comply to Energy Star "Green PC" Program  
Supports Alarm Wake Up  
Supports Modem Ring On  
Trend Micro's Chip Away Virus and PC-Cillin included

All brand names and registered trademarks mentioned are property of their owners

---