


## NS GX1-300 SBC with VGA/LCD/2xLAN /Sound/TV/GPS/CompactFlash



# EM-351A

SBC



## FEATURES

- On-board low power CPU (NS Geode™ GX1-300 MHz)
- NS Geode™ CS5530A, display memory shared with system memory 2MB
- One SODIMM socket
- Built-in VGA/LCD/TV and sound functions, Support multimedia application
- Support Dual-10/100 Base-T interface
- Sockets for CompactFlash
- Reserved Header for GPS module
- Four COM ports and two parallel ports
- 3.5" form factor

## SPECIFICATION

**CPU** NS Geode™ GX1-300 MHz Lower Power CPU on-board

**Chipset** NS CS5530A

**BIOS** 256KB Award® license BIOS

**System Memory** 1x144-pin SODIMM socket, support up to 128MB SDRAM

### VGA/LCD

NS CS5530A, shared memory 2MB, resolution up to 1024 x 768 @ 64K Colors

### TV Output

NTSC/PAL mode, support Composite /S-Video /R-G-B output

### Sound Output

Built-in sound functions, include Mic- in/ Speaker-out connectors

### Ethernet

2 Realtek RTL8139C, support 10 /100 Base-TX interface

### Flash Memory Disk

Reserved socket for DiskOnChip® from M-System, support up to 72 MB flash memory disk

**GPS connector** Reserved Header for GPS Kit

**CompactFlash Socket** 1 CompactFlash Socket, support ATA mode, Type II

### IDE Interface

1 PCI IDE port, support up to 2 IDE devices. Support PIO mode 4 and Bus Master. Also support Multi-word DMA and Ultra DMA/33.

### Floppy Drive Interface

1 FDD port , support 1 Floppy device

### Serial Port

4 COM ports ,3 RS-232 and 1 RS-232/422 /485

### Parallel Port

2 Multi-mode parallel ports(SPP/EPP/ECP)

### Keyboard/Mouse connector

1x 6-pin mini-DIN PS/2 keyboard/mouse connector on-board.

**Universal Serial Bus** Support 2 USB ports

**IR Interface** Support 1 IrDA header

**RTC** : Internal RTC with Li battery

**Power Connector** On-board 4-pin power Connector (NC, GND, GND, +5)

**Power Management** I/O peripheral devices support power saving and doze/standby/ suspend modes. APM 1.2 compliant.

### Power Consumption

+5V@2.1A (GX1-233MHz, 128MB SDRAM)

**Operating Temperature** 0°C ~ 60°C

**Storage Temperature** -10°C ~ 70°C

### Humidity

5% ~ 95% RH, non-condensing

### Dimensions

145 x 102 mm (5 3/4" x 4")

### Net Weight

250 g ( 0.55 pounds )