

AMIBIOS HIFLEX SETUP UTILITY - VERSION 1.23b
(C)1999 American Megatrends, Inc. All Rights Reserved

Standard CMOS Setup
Advanced CMOS Setup
Advanced Chipset Setup
Power Management Setup
PCI / Plug and Play Setup
Peripheral Setup
Hardware Monitor Setup
Auto-Detect Hard Disks
Change User Password
Change Supervisor Password
Change Language Setting
Auto Configuration with Optimal Settings
Auto Configuration with Fail Safe Settings
Save Settings and Exit
Exit Without Saving

Standard CMOS setup for changing time, date, hard disk type, etc.
ESC:Exit ↑↓:Sel F2/F3:Color F10:Save & Exit

AMIBIOS SETUP - STANDARD CMOS SETUP

(C)1999 American Megatrends, Inc. All Rights Reserved

Date (mm/dd/yyyy): Sat Jun 24, 2000
 Time (hh/mm/ss) : 14:48:07

Base Memory: 0 KB
 Extd Memory: 0 MB

Floppy Drive A: 1.44 MB 3½
 Floppy Drive B: Not Installed

	Type	Size	Cyln	Head	WPcom	Sec	LBA Mode	Blk Mode	PIO Mode	32Bit Mode
Pri Master :	Not Installed									
Pri Slave :	Not Installed									
Sec Master :	Not Installed									
Sec Slave :	Not Installed									

Use Auto Detect
 Hard Disks Option

Boot Sector Virus Protection Disabled

ESC:Exit ↑↓:Sel
 PgUp/PgDn:Modify
 F1:Help F2/F3:Color

AMIBIOS SETUP - ADVANCED CMOS SETUP

(C)1999 American Megatrends, Inc. All Rights Reserved

Quick Boot	Enabled
1st Boot Device	Floppy
2nd Boot Device	IDE-0
3rd Boot Device	CDROM
Try Other Boot Devices	Yes
Initial Display Mode	BIOS
Floppy Access Control	Read-Write
S.M.A.R.T. for Hard Disks	Enabled
BootUp Num-Lock	On
Floppy Drive Swap	Disabled
Floppy Drive Seek	Enabled
PS/2 Mouse Support	Enabled
Primary Display	VGA/EGA
Password Check	Setup
Boot To OS/2 > 64MB	No
Wait For 'F1' If Error	Enabled
CPU Serial Number	Enabled
L1 Cache	WriteBack
L2 Cache	WriteBack
Cache Bus ECC	Enabled

Available Options:

- Disabled
- ▶ Enabled

ESC:Exit ↑↓:Sel
 PgUp/PgDn:Modify
 F1:Help F2/F3:Color

AMIBIOS SETUP - ADVANCED CMOS SETUP

(C)1999 American Megatrends, Inc. All Rights Reserved

3rd Boot Device	CDROM
Try Other Boot Devices	Yes
Initial Display Mode	BIOS
Floppy Access Control	Read-Write
S.M.A.R.T. for Hard Disks	Enabled
BootUp Num-Lock	On
Floppy Drive Swap	Disabled
Floppy Drive Seek	Enabled
PS/2 Mouse Support	Enabled
Primary Display	VGA/EGA
Password Check	Setup
Boot To OS/2 > 64MB	No
Wait For 'F1' If Error	Enabled
CPU Serial Number	Enabled
L1 Cache	WriteBack
L2 Cache	WriteBack
Cache Bus ECC	Enabled
System BIOS Cacheable	Enabled
C000,64k Shadow	Disabled
D000,64k Shadow	Disabled

Available Options:

- ▶ Disabled
- Enabled
- Cached

ESC:Exit ↑↓:Sel
PgUp/PgDn:Modify
F1:Help F2/F3:Color

AMIBIOS SETUP - ADVANCED CHIPSET SETUP
(C)1999 American Megatrends, Inc. All Rights Reserved

USB Function	Enabled
USB KB/Mouse/FDD Legacy Support	Disabled
CAS# Latency (SCLKs)	Auto
Graphics Mode Select	Reserved
ICH Delayed Transaction	Disabled
ClkGen Spread Spectrum	Enabled
ClkGen for PCI Slot/DIMM	Enabled
**** Display Cache Function ****	
Init Display Cache Memory	Enabled
Paging Mode Control	Open
RAS-to-CAS	Default
CAS Latency	Fast
RAS Timing	Fast
RAS Precharge Timing	Fast

Available Options:
Disabled
▶ Enabled

Set to CLOSE



ESC:Exit ↑↓:Sel
PgUp/PgDn:Modify
F1:Help F2/F3:Color

AMIBIOS SETUP - POWER MANAGEMENT SETUP

(C)1999 American Megatrends, Inc. All Rights Reserved

ACPI Standby State	S1
Power Management/APM	Enabled
Video Power Down Mode	Disabled
Hard Disk Power Down Mode	Disabled
Standby Time Out (Minute)	Disabled
Suspend Time Out (Minute)	Disabled
System Thermal	Ignore
Power Button Function	On/Off
Resume On Ring	Disabled
Wake On LAN Function	Enabled
PCI PME Function Support	Enabled
Resume On RTC Alarm	Disabled
RTC Alarm Date	Every Day
RTC Alarm Hour	00
RTC Alarm Minute	00
RTC Alarm Second	00
PowerLoss Control	Off
Mouse Power On function	Disabled
Keyboard Power On function	Disabled

Available Options:

- ▶ S1
- S3

ESC:Exit ↑↓:Sel
PgUp/PgDn:Modify
F1:Help F2/F3:Color

AMIBIOS SETUP - PCI / PLUG AND PLAY SETUP
(C)1999 American Megatrends, Inc. All Rights Reserved

Plug and Play Aware O/S	Yes
Clear NVRAM	Yes
PCI Latency Timer	64
Primary Graphics Adapter	OnBoard VGA
PCI IDE BusMaster	Enabled
PCI Slot1/Slot5 IRQ Priority	Auto
PCI Slot2 IRQ Priority	Auto
PCI Slot3 IRQ Priority	Auto
PCI Slot4 (Onbd. Audio) IRQ Pri	Auto
IRQ3	Available
IRQ4	Available
IRQ5	Available
IRQ7	Available
IRQ9	Available
IRQ10	Available
IRQ11	Available
IRQ14	Available
IRQ15	Available

Available Options:

- No
- ▶ Yes

ESC:Exit ↑↓:Sel
PgUp/PgDn:Modify
F1:Help F2/F3:Color

AMIBIOS SETUP - PERIPHERAL SETUP

(C)1999 American Megatrends, Inc. All Rights Reserved

OnBoard Audio	Enabled		
OnBoard AC'97 Audio	Disabled		
OnBoard AC'97 Modem	Disabled		
OnBoard IDE	Both	▶	378
OnBoard FDC	Auto	◀	278
OnBoard Serial PortA	Auto	◀	3BC
OnBoard Serial PortB	Auto	◀	
Serial PortB Mode	Normal		Set to 2F8
IR Duplex Mode	Half Duplex		
OnBoard Parallel Port	378		
Parallel Port Mode	Normal		
Parallel Port IRQ	5	◀	Set to IRQ 7
Parallel Port DMA	N/A		

Available Options:

Auto

Disabled

ESC:Exit ↑↓:Sel

PgUp/PgDn:Modify

F1:Help F2/F3:Color

AMIBIOS SETUP - HARDWARE MONITOR SETUP

(C)1999 American Megatrends, Inc. All Rights Reserved

CPU Ratio Selection	6.0x
--≡ System Hardware Monitor ≡--	
Chassis Intrusion	Disabled
Current CPU Temperature	59°C
Current System Temperature	27°C
Current CPU Fan Speed	3200 RPM
Current Chassis Fan Speed	0 RPM
VID from CPU	1.60V
CPU VCore(VID)	1.61V
+5.0V	5.15V
Vtt 1.5V	1.52V
+1.8V	1.84V
+12V	11.95V
-12V	-12.35V
USB +3.3V	3.36V
VDD +3.3V	3.38V

Available Options:

3.0x
3.5x
4.0x
4.5x
5.0x
5.5x
6.0x
6.5x
7.0x
7.5x
8.0x

Depends on CPU Type

ESC:Exit ↑↓:Sel
PgUp/PgDn:Modify
F1:Help F2/F3:Color